

DRILLING DEPTH RATING: 30,000'

LIGHTSHIP:

(Overall Average Draft) 7'
 (Towing Height) 66.7'

BARGE DIMENSIONS, SPECIFICATIONS:

Length 230'
 Beam 64'
 Hull Depth 14'
 Posted Deck Height 14'
 Key Slot 40 X 10'
 Main Deck to Rotary Pan 30'
 Main Deck to Top of Rotary 35'
 Main deck to Bottom of Trolley Beams 25'
 Accommodations 60 bunks
 Helipad 68' X 50'

CAPACITIES:

Potable water 63,000 gallons
 Drill water 5,100 barrels
 Fuel 75,000 gallons
 Mud tank capacity: 1,810 barrels
 Bulk Barite 4,000 sacks
 Tear-Drop Bulk Barite 75 sacks



Equipped for full zero discharge operations for work within environmentally sensitive areas.

DRAWWORKS:

- Continental Emsco C-3 Type II (3000 hp)
 w/15050 Elmago elec. brake, driven by (3) GE
 752 elec. motors (3000 hp)

MUD PUMPS:

-(3) LEWCO W-2215 (2200 hp ea) pumps,
 each driven by (2) GE-752 Hi-Torque electric
 motors (1130 hp each)
 - 7500 psi wp Working Pressure Mud System

MAST AND TRAVELING EQUIPMENT:

- 156' DSI cantilever mast, w/static hook load of 2,000,000 lbs
 - 750T DSI 8 sheave crown grooved for 1 5/8" drill line
 - 750T Traveling Block
 - 750T CanRig Top Drive Unit (AC)
 - 37 1/2" Rotary Table
 - (1) 7500 psi wp Rotary Hose

WELL CONTROL EQUIPMENT:

- (1) 13 5/8" 5,000 psi Annular BOP
 - (1) 13 5/8" 10,000 psi Cameron Type U Single Ram BOP
 - (1) 13 5/8" 10,000 psi Cameron Type U Double Ram BOP w/
 LBSBTB blind shear rams
 - (1) 13 5/8" 10,000 lb. Drilling Spool
 - 240 gal. Koomey Accumulator and Closing Unit
 - 10,000 psi Choke Manifold

Note: Other BOP equipment available from stock

Note: equipment subject to client-specific requirements



Energy. Well engineered.

Find out more at parkerwellbore.com

©2021 Parker Wellbore. All Rights Reserved.



1005 RPC Energy Dr. Broussard, LA 70518
 Tel: 337.364.3122 Fax: 337.364-3292
 Uncontrolled if printed • Date of issue 09/21/07

- Shale Shaker	(1) Derrick Primer shaker FLP 28/258 + (4) Derrick Hyperpool 4 Panel
- Desilter	(3) Derrick 10" Hypercyclone
- Desander	(20) Derrick 4" Hypercyclone
- Degasser	Brandt DG-10
- Mud Agitators	(1) Brandt MA-25 + (4) MA-15 + (2) MA-5
- Mud Mixing Pumps	(3) 6 X 8 centrifugal pumps w/100 HP motors (2) Vortex shear hoppers – equipped with dust recovery system

- (4) D-3516 BHD Caterpillar (2150 hp) engines
- (4) KATO 1800 kw generator sets
- (5) Bay SIEMENS Digital SCR System

- (2) 30T cranes w/70' booms
- (2) 50 bbl trip tanks
- (2) Quincy Model 245-A compressors (rig air)
- (1) Quincy Model QSI 60 LP compressor (bulk air)
- (1) Ingersoll Rand cold start air compressor
- (1) 10' x 30' + (2) 12' x 30' cantilever deck – Port Side
- (1) .092 Wireline unit
- (1) 950 Spin Master pipe spinner
- 90' Mouse Hole

